

# Cat<sup>®</sup> Coolant

EAME

Cat offers extended life coolant which protects high-performing equipment and helps support customer's investments. Two options of extended life coolant include Cat ELC which contains Glycol and Cat ELI which is water based coolant that does not contain Glycol. Cat ELC and ELI provide industry leading corrosion resistance and longer engine life. This coolant uses Organic Acid Technology (OAT) with additives extending the life of the coolant without the need for supplemental coolant additive (SCA).

Cat DEAC and Cat NGEC offer conventional coolant proven technology which is an option for customers looking for lower up-front cost. Although it is less expensive up front, the over all lifetime cost is higher because DEAC/NGEC requires the need for SCA and frequent maintenance.

## ELC

- Caterpillars factory-fill recommended premium product
- Reduces engine coolant and additive costs by as much as 500% compared to conventional coolants
- Longest lasting coolant product available
- Available in premixed & concentrate
- Incorporates an advanced formula technology

EAME Part Number	Litres	Gallons
205-6611	5	1.32
205-6612	20	5.3
205-6613	210	55.5
205-6614	1000	264.2
205-6615*	5	1.32



\* Concentrate

## ELI

- Lasts three to six times longer than conventional coolants or commercial supplemental coolant additives (SCA) mixed with water. Allows for less frequent: checks of coolant health, replacement of inhibitors, and drains/flushes
- Available in Concentrate
- No Glycol = No freeze protection

EAME Part Number	Litres	Gallons
387-2877	20	5.3
387-2878	210	55.5



## DEAC

- Protects the cooling system in your equipment over a temperature range of -34°F (-37°C) to 265°F (129°C) when used as a 50/50 percent mix with water
- Contains conventional coolant inhibitors providing superior protection for metal components, especially aluminum, against pitting and corrosion
- Formulation minimizes the formation of foam
- Available in Concentrate

EAME Part Number	Litres	Gallons
362-2180	5	1.32
362-2181	210	55.5



## NGEC

- Protects the cooling system of your natural gas engine over a temperature range of -34°F (-37°C) to 265°F (129°C)
- Designed to prevent freezing and boiling while providing superior component protection
- Approved for use in all Cat natural gas and diesel engines
- Available in Premixed

EAME Part Number	Litres	Gallons
362-2182	210	55.5



PEWJ0213  
www.cat.com

© 2013 Caterpillar • All Rights Reserved • Printed in USA  
CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow", the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

